

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Cordless jigsaw 18.0 V

JS 18.0-EC C

Order number 485.403



Cordless jigsaw 18.0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + New generation of brushless motors delivering high efficiency and performance
- + With automatic start-up, overload protection
- + Continuously variable cutting speed setting via potentiometer wheel with automatic start-up in position "A"
- + Electronic switch can be operated from both sides
- + Orbital stroke: 4 settings for higher cutting rate
- + Tool-free saw blade change with quick-clamping system and eject function
- + Double roller jigsaw blade guide for precise cuts with accurate angles
- + Removable chip screen, for tear-free cuts and for guiding the saw blade
- + Saw bench adjustment for bevel cuts of up to 45°, 0-lock. Can be set off backwards for sawing close to edges
- + Stable base plate with removable plastic guide block for the protection of delicate surfaces
- + Vacuum flange Ø 27 mm, for a cleaner workplace and clear view of the cut
- + Free view of the marking thanks to integrated blow function
- + Perfect ergonomics thanks to ideally located SoftGrip surfaces
- + Integrated LED lamp for optimum illumination of the work area.
- + Low-vibration and comfortable sawing
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18,0 V battery packs. Delivery does not include battery and charger

Technical attributes

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Orbit rate, no load	0-3500 opm
Orbit	26 mm
Pendulum stroke levels	4
Speed settings	1-5 + A
Pivoting range	0-45 °
Max. cutting depth in wood	120 mm
Max. material thickness in steel sheet	8 mm
Size (W x L x H)	275 x 82 x 197 mm
Weight without battery	2,1 kg

Standard equipment

1 guide block	490.237
1 hexagon socket wrench, SW 4	102.229
1 protection against flying swarf, closed	1 piece
1 anti-splinter guard	490.229
1 extraction adapter	490.245