



TAKTEC®

SURFACE PROTECTION FILMS

	CARPET PROTECTION FILM						HARD SURFACE PROTECTION FILM		
CODE	172099	172100	172104	172105	172106	172107	172101	172102	172103
Thickness (mu)	60	60	60	80	80	80	50	50	50
Width (mm)	600	600	600	600	900	1200	600	600	600
Length (m)	50	100	100	100	100	100	50	100	100
Colour	White	White	White	White	White	White	Green	Green	Green
Flame Retardant	NA	NA	NA	FR	FR	FR	NA	NA	NA
Film	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE	LDPE+LLDPE
Adhesive	PSA	PSA	PSA	PSA	PSA	PSA	PSA	PSA	PSA
Elongation	300%	300%	300%	300%	300%	300%	300%	300%	300%
Tensile	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm	2.75kg/25mm
Adhesion	650gf/25mm +/-20%	650gf/25mm +/-20%	650gf/25mm +/-20%	650gf/25mm +/-20%	650gf/25mm +/-20%	650gf/25mm +/-20%	120gf/25mm +/-20%	120gf/25mm +/-20%	120gf/25mm +/-20%
Max Usage	30 Days	30 Days	30 Days	30 Days	30 Days	30 Days	30 Days	30 Days	30 Days

Not suitable for use on wool, silk or handmade carpets

Not suitable for use on painted or varnished wood surfaces.

Max usage times will change if underfloor heating is present - Test on surface prior to use - Swiftec take no responsibility for damage as a result of improper use of this product.



**WATERPROOF
TECHNOLOGY**



**IDEAL FOR
STAIRS**



**SIMPLE TO
INSTALL**



**LEAVES NO
RESIDUE**



**IDEAL ON SMOOTH
SURFACES
(H5 GRADE ONLY)**



**PAINT SPILL
PROTECTION**



www.taktec-film.com



info.global@taktec-film.com

swiftec
group