

TAKTEC® HARD SURFACE PROTECTION FILM USER GUIDE AND WARNINGS

- Simple to apply and remove. Do not leave down for more than 30 days.
- Please avoid storing at extreme temperatures.
- Manufactured to suit most hard surfaces that are free from dust. Always test on a non critical area first.
- **DO NOT USE** on any painted or varnished surface.
- **DO NOT USE** on freshly laid wood floors that need to cure.
- **DO NOT USE** on any floor that needs to cure, i.e. screeded floors or newly laid marble floors.
- **DO NOT USE** if underfloor heating is switched on, or if floor is still warm from its use.
- It is the purchaser/user's responsibility to check suitability for the use of this product and therefore assumes all risk in connection with its use.
- Taktec® Hard surface film is a single use product.
- Taktec® Hard surface film may in certain situations leave a residue, this can easily be removed using warm soapy water.
- Taktec® Hard surface film is much safer than loose dust sheets but may be slippery when wet.

This spec sheet was correct at time of going to print but visit www.antinoxglobal.com for the latest version. Taktec® take no responsibility for damage as a result of improper use of this product.



WATERPROOF TECHNOLOGY



IDEAL FOR STAIRS



SIMPLE TO INSTALL



LEAVES NO RESIDUE



IDEAL ON SMOOTH SURFACES (H5 GRADE ONLY)



PAINT SPILL PROTECTION

